


# SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2015/830

# Silirub 2



Revision number: 0503

# SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General:

If you feel unwell, seek medical advice.

### After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

# After skin contact:

Wash immediately with lots of water. Soap may be used. Take victim to a doctor if irritation persists.

### After eye contact:

Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Take victim to an ophthalmologist if irritation persists.

Rinse mouth with water. Consult a doctor/medical service if you feel unwell.

# 4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms After inhalation: No effects known. After skin contact: No effects known. After eye contact: No effects known. After ingestion: No effects known. 4.2.2 Delayed symptoms No effects known.

4.3. Indication of any immediate medical attention and special treatment needed If applicable and available it will be listed below.

# SECTION 5: Firefighting measures

- 5.1. Extinguishing media
  - 5.1.1 Suitable extinguishing media: Polyvalent foam. ABC powder. Carbon dioxide.
  - 5.1.2 Unsuitable extinguishing media: No unsuitable extinguishing media known.
- 5.2. Special hazards arising from the substance or mixture Upon combustion: formation of CO, CO2 and small quantities of nitrous vapours and formation of metallic fumes.

# 5.3. Advice for firefighters

- 5.3.1 Instructions:
- No specific fire-fighting instructions required.
- 5.3.2 Special protective equipment for fire-fighters:
  - Gloves. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

# SECTION 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

- No naked flames.
- 6.1.1 Protective equipment for non-emergency personnel See heading 8.2
- 6.1.2 Protective equipment for emergency responders Gloves. Protective clothing.
  - Suitable protective clothing
  - See heading 8.2

### 6.2. Environmental precautions

Contain released product. Use appropriate containment to avoid environmental contamination.

# 6.3. Methods and material for containment and cleaning up

Scoop solid spill into closing containers. Clean contaminated surfaces with a soap solution. Wash clothing and equipment after handling.

# 6.4. Reference to other sections

See heading 13.

Reason for revision: 15.1

	Silirub 2		
CTION 7: Handling and			
CTION 7: Handling and s		ure scenaries are attached in annou	Always use the relevant experim
scenarios that correspond to your identif	al description. If applicable and available, exposied use.	ure scenarios are attached in annex.	Always use the relevant exposure
7.1. Procentions for safe handlin			
7.1. Precautions for safe handlin Keep away from naked flames/heat. C	Dbserve strict hygiene. Keep container tightly clo	osed.	
7.2. Conditions for safe storage, 7.2.1 Safe storage requirements:	including any incompatibilities		
<b>e</b> 1	temperature. Meet the legal requirements. Ma	<. storage time: 1 year(s).	
7.2.2 Keep away from:			
Heat sources. 7.2.3 Suitable packaging material:			
Synthetic material.			
7.2.4 Non suitable packagin <mark>g materia</mark>	al:		
No data available			
7.3. Specific end use(s)			
If applicable and available, exposu	ire scenarios are attached in annex. See informa	tion supplied by the manufacturer.	
CTION 8: Exposure cont	rols/personal protection		
8.1. Control parameters			
8.1.1 Occupational exposure			
a) Occupational exposure limit va If limit values are applicable and a	_		
in infint values are applicable and a	valiable these will be listed below.		
Germany	Per una ser a la l		0.2
Butanonoxim		erage exposure limit 8 h (TRGS 900) erage exposure limit 8 h (TRGS 900)	0.3 ppm 1 mg/m³
b) National biological limit values			
If limit values are applica <mark>ble and a</mark>			
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values <u>DNEL/DMEL - Workers</u>	e listed below. sing the substance or mixture as intended		
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values <u>DNEL/DMEL - Workers</u> <u>2-butanone oxime</u>	e listed below. sing the substance or mixture as intended vailable these will be listed below.	Value	Remark
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values <u>DNEL/DMEL - Workers</u>	e listed below. sing the substance or mixture as intended vailable these will be listed below. Type Long-term systemic effects inhalation	Value 9 mg/m <sup>3</sup>	Remark
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values <u>DNEL/DMEL - Workers</u> <u>2-butanone oxime</u> Effect level (DNEL/DMEL)	e listed below. sing the substance or mixture as intended vailable these will be listed below. Type Long-term systemic effects inhalation Long-term local effects inhalation	9 mg/m³ 3.33 mg/m³	Remark
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values <u>DNEL/DMEL - Workers</u> <u>2-butanone oxime</u> Effect level (DNEL/DMEL)	e listed below. sing the substance or mixture as intended vailable these will be listed below. Type Long-term systemic effects inhalation Long-term local effects inhalation Long-term systemic effects dermal	9 mg/m³ 3.33 mg/m³ 1.3 mg/kg bw/day	Remark
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values <u>DNEL/DMEL - Workers</u> <u>2-butanone oxime</u> Effect level (DNEL/DMEL)	e listed below. sing the substance or mixture as intended vailable these will be listed below. Type Long-term systemic effects inhalation Long-term local effects inhalation Long-term systemic effects dermal Acute systemic effects dermal	9 mg/m³ 3.33 mg/m³	Remark
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values <u>DNEL/DMEL - Workers</u> <u>2-butanone oxime</u> <u>Effect level (DNEL/DMEL)</u> DNEL <u>DNEL/DMEL - General population</u> <u>2-butanone oxime</u>	e listed below. sing the substance or mixture as intended vailable these will be listed below. Type Long-term systemic effects inhalation Long-term local effects inhalation Long-term systemic effects dermal Acute systemic effects dermal	9 mg/m³ 3.33 mg/m³ 1.3 mg/kg bw/day 2.5 mg/kg bw/day	
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values <u>DNEL/DMEL - Workers</u> <u>2-butanone oxime</u> <u>Effect level (DNEL/DMEL)</u> <u>DNEL</u> <u>DNEL/DMEL - General population</u> <u>2-butanone oxime</u> <u>Effect level (DNEL/DMEL)</u>	e listed below. sing the substance or mixture as intended vailable these will be listed below. Type Long-term systemic effects inhalation Long-term local effects inhalation Long-term systemic effects dermal Acute systemic effects dermal I Type	9 mg/m³ 3.33 mg/m³ 1.3 mg/kg bw/day 2.5 mg/kg bw/day Value	Remark
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values <u>DNEL/DMEL - Workers</u> <u>2-butanone oxime</u> <u>Effect level (DNEL/DMEL)</u> DNEL <u>DNEL/DMEL - General population</u> <u>2-butanone oxime</u>	e listed below. sing the substance or mixture as intended vailable these will be listed below. Type Long-term systemic effects inhalation Long-term local effects inhalation Long-term systemic effects dermal Acute systemic effects dermal Type Long-term systemic effects inhalation Long-term systemic effects inhalation	9 mg/m³ 3.33 mg/m³ 1.3 mg/kg bw/day 2.5 mg/kg bw/day	
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values <u>DNEL/DMEL - Workers</u> <u>2-butanone oxime</u> <u>Effect level (DNEL/DMEL)</u> <u>DNEL</u> <u>DNEL/DMEL - General population</u> <u>2-butanone oxime</u> <u>Effect level (DNEL/DMEL)</u>	e listed below. sing the substance or mixture as intended vailable these will be listed below. Type Long-term systemic effects inhalation Long-term local effects inhalation Long-term systemic effects dermal Acute systemic effects dermal Type Long-term systemic effects inhalation Long-term systemic effects inhalation Long-term local effects inhalation Long-term systemic effects inhalation Long-term systemic effects dermal	9 mg/m <sup>3</sup> 3.33 mg/m <sup>3</sup> 1.3 mg/kg bw/day 2.5 mg/kg bw/day Value 2.7 mg/m <sup>3</sup> 2 mg/m <sup>3</sup> 0.78 mg/kg bw/day	
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values DNEL/DMEL - Workers 2-butanone oxime Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL Effect level (DNEL/DMEL) DNEL DNEL DNEL	e listed below. sing the substance or mixture as intended vailable these will be listed below. Type Long-term systemic effects inhalation Long-term local effects inhalation Long-term systemic effects dermal Acute systemic effects dermal Type Long-term systemic effects inhalation Long-term systemic effects inhalation	9 mg/m <sup>3</sup> 3.33 mg/m <sup>3</sup> 1.3 mg/kg bw/day 2.5 mg/kg bw/day Value 2.7 mg/m <sup>3</sup> 2 mg/m <sup>3</sup>	
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values DNEL/DMEL - Workers 2-butanone oxime Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL PNEC 2-butanone oxime	e listed below. sing the substance or mixture as intended vailable these will be listed below. Type Long-term systemic effects inhalation Long-term local effects inhalation Long-term systemic effects dermal Acute systemic effects dermal Long-term systemic effects inhalation Long-term systemic effects inhalation Long-term systemic effects inhalation Long-term systemic effects inhalation Long-term systemic effects dermal Acute systemic effects dermal Acute systemic effects dermal	9 mg/m <sup>3</sup> 3.33 mg/m <sup>3</sup> 1.3 mg/kg bw/day 2.5 mg/kg bw/day Value 2.7 mg/m <sup>3</sup> 2 mg/m <sup>3</sup> 0.78 mg/kg bw/day 1.5 mg/kg bw/day	
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values DNEL/DMEL - Workers 2-butanone oxime Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL PNEC 2-butanone oxime Compartments	e listed below. sing the substance or mixture as intended vailable these will be listed below. Type Long-term systemic effects inhalation Long-term local effects inhalation Long-term systemic effects dermal Acute systemic effects dermal Long-term systemic effects inhalation Long-term systemic effects inhalation Long-term systemic effects inhalation Long-term systemic effects inhalation Long-term systemic effects dermal Acute systemic effects dermal	9 mg/m <sup>3</sup> 3.33 mg/m <sup>3</sup> 1.3 mg/kg bw/day 2.5 mg/kg bw/day Value 2.7 mg/m <sup>3</sup> 2 mg/m <sup>3</sup> 0.78 mg/kg bw/day	
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values DNEL/DMEL - Workers 2-butanone oxime Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL PNEC 2-butanone oxime Compartments Fresh water	e listed below. sing the substance or mixture as intended vailable these will be listed below. Type Long-term systemic effects inhalation Long-term local effects inhalation Long-term systemic effects dermal Acute systemic effects dermal Long-term systemic effects inhalation Long-term local effects inhalation Long-term local effects inhalation Long-term local effects inhalation Long-term systemic effects dermal Acute systemic effects dermal	9 mg/m <sup>3</sup> 3.33 mg/m <sup>3</sup> 1.3 mg/kg bw/day 2.5 mg/kg bw/day Value 2.7 mg/m <sup>3</sup> 2 mg/m <sup>3</sup> 0.78 mg/kg bw/day 1.5 mg/kg bw/day	
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values DNEL/DMEL - Workers 2-butanone oxime Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL PNEC 2-butanone oxime Compartments	e listed below. sing the substance or mixture as intended vailable these will be listed below. Type Long-term systemic effects inhalation Long-term local effects inhalation Long-term systemic effects dermal Acute systemic effects dermal Long-term systemic effects inhalation Long-term systemic effects inhalation Long-term systemic effects inhalation Long-term systemic effects inhalation Long-term systemic effects dermal Acute systemic effects dermal	9 mg/m <sup>3</sup> 3.33 mg/m <sup>3</sup> 1.3 mg/kg bw/day 2.5 mg/kg bw/day Value 2.7 mg/m <sup>3</sup> 2 mg/m <sup>3</sup> 0.78 mg/kg bw/day 1.5 mg/kg bw/day	
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values DNEL/DMEL - Workers 2-butanone oxime Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL DNEL PNEC 2-butanone oxime Compartments Fresh water Aqua (intermittent releases) STP 8.1.5 Control banding	e listed below. sing the substance or mixture as intended vailable these will be listed below. Type Long-term systemic effects inhalation Long-term systemic effects dermal Acute systemic effects dermal Acute systemic effects inhalation Long-term systemic effects inhalation Long-term local effects inhalation Long-term local effects inhalation Long-term systemic effects inhalation Long-term systemic effects dermal Acute systemic effects dermal	9 mg/m <sup>3</sup> 3.33 mg/m <sup>3</sup> 1.3 mg/kg bw/day 2.5 mg/kg bw/day Value 2.7 mg/m <sup>3</sup> 2 mg/m <sup>3</sup> 0.78 mg/kg bw/day 1.5 mg/kg bw/day	
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values DNEL/DMEL - Workers 2-butanone oxime Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL PNEC 2-butanone oxime Compartments Fresh water Aqua (intermittent releases) STP 8.1.5 Control banding If applicable and available it will be 8.2. Exposure controls The information in this section is a ger scenarios that correspond to your ide 8.2.1 Appropriate engineering control	e listed below. sing the substance or mixture as intended vailable these will be listed below. I ype Long-term systemic effects inhalation Long-term systemic effects dermal Acute systemic effects dermal Acute systemic effects inhalation Long-term systemic effects inhalation Long-term systemic effects dermal Acute systemic effects dermal Acute systemic effects dermal Acute systemic effects dermal Dog-term systemic effects dermal Acute systemic effe	9 mg/m <sup>3</sup> 3.33 mg/m <sup>3</sup> 1.3 mg/kg bw/day 2.5 mg/kg bw/day 2.5 mg/m <sup>3</sup> 2.7 mg/m <sup>3</sup> 2.7 mg/m <sup>3</sup> 0.78 mg/kg bw/day 1.5 mg/kg bw/day	Remark         Image: Second
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values DNEL/DMEL - Workers 2-butanone oxime Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL PNEC 2-butanone oxime Compartments Fresh water Aqua (intermittent releases) STP 8.1.5 Control banding If applicable and available it will be 8.2. Exposure controls The information in this section is a ger scenarios that correspond to your ide 8.2.1 Appropriate engineering control Keep away from naked flames/hee 8.2.2 Individual protection measures	e listed below. sing the substance or mixture as intended vailable these will be listed below. Type Long-term systemic effects inhalation Long-term local effects inhalation Long-term systemic effects dermal Acute systemic effects dermal Acute systemic effects inhalation Long-term systemic effects inhalation Long-term systemic effects dermal Acute systemic eff	9 mg/m <sup>3</sup> 3.33 mg/m <sup>3</sup> 1.3 mg/kg bw/day 2.5 mg/kg bw/day 2.5 mg/kg bw/day 2.7 mg/m <sup>3</sup> 2.7 mg/m <sup>3</sup> 0.78 mg/kg bw/day 1.5 mg/kg bw/day  Remark  bosure scenarios are attached in ann haust/ventilation or with respiratory	Remark         Image: Second
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values <u>DNEL/DMEL - Workers</u> <u>2-butanone oxime</u> <u>Effect level (DNEL/DMEL)</u> DNEL <u>DNEL/DMEL - General population</u> <u>2-butanone oxime</u> <u>Effect level (DNEL/DMEL)</u> DNEL <u>DNEL</u> <u>DNEL</u> <u>DNEL</u> <u>PNEC</u> <u>2-butanone oxime</u> <u>Compartments</u> <u>Fresh water</u> <u>Aqua (intermittent releases)</u> <u>STP</u> 8.1.5 Control banding If applicable and available it will be 8.2. Exposure controls The information in this section is a gen scenarios that correspond to your ide 8.2.1 Appropriate engineering control Keep away from naked flames/hee 8.2.2 Individual protection measures Observe strict hygiene. Keep controls	e listed below. sing the substance or mixture as intended vailable these will be listed below. Type Long-term systemic effects inhalation Long-term local effects inhalation Long-term systemic effects dermal Acute systemic effects dermal Acute systemic effects inhalation Long-term systemic effects inhalation Long-term local effects inhalation Long-term systemic effects dermal Acute systemi	9 mg/m <sup>3</sup> 3.33 mg/m <sup>3</sup> 1.3 mg/kg bw/day 2.5 mg/kg bw/day 2.5 mg/kg bw/day 2.7 mg/m <sup>3</sup> 2.7 mg/m <sup>3</sup> 0.78 mg/kg bw/day 1.5 mg/kg bw/day  Remark  bosure scenarios are attached in ann haust/ventilation or with respiratory	Remark         Image: Second
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values DNEL/DMEL - Workers 2-butanone oxime Effect level (DNEL/DMEL) DNEL DNEL DNEL Effect level (DNEL/DMEL) DNEL Effect level (DNEL/DMEL) DNEL DNEL PNEC 2-butanone oxime Compartments Fresh water Aqua (intermittent releases) STP 8.1.5 Control banding If applicable and available it will be 8.2. Exposure controls The information in this section is a ger scenarios that correspond to your ide 8.2.1 Appropriate engineering control Keep away from naked flames/hei 8.2.2 Individual protection:	e listed below. sing the substance or mixture as intended vailable these will be listed below. Type Long-term systemic effects inhalation Long-term local effects inhalation Long-term systemic effects dermal Acute systemic effects dermal Acute systemic effects inhalation Long-term systemic effects inhalation Long-term systemic effects dermal Acute systemic eff	9 mg/m <sup>3</sup> 3.33 mg/m <sup>3</sup> 1.3 mg/kg bw/day 2.5 mg/kg bw/day 2.5 mg/kg bw/day 2.7 mg/m <sup>3</sup> 2 mg/m <sup>3</sup> 0.78 mg/kg bw/day 1.5 mg/kg bw/day Remark posure scenarios are attached in ann maust/ventilation or with respiratory during work.	ex. Always use the relevant expo
8.1.2 Sampling methods If applicable and available it will be 8.1.3 Applicable limit values when us If limit values are applicable and a 8.1.4 DNEL/PNEC values <u>DNEL/DMEL - Workers</u> <u>2-butanone oxime</u> <u>Effect level (DNEL/DMEL)</u> DNEL <u>DNEL/DMEL - General population</u> <u>2-butanone oxime</u> <u>Effect level (DNEL/DMEL)</u> DNEL <u>DNEL</u> <u>DNEL</u> <u>DNEL</u> <u>PNEC</u> <u>2-butanone oxime</u> <u>Compartments</u> <u>Fresh water</u> <u>Aqua (intermittent releases)</u> <u>STP</u> 8.1.5 Control banding If applicable and available it will be 8.2. Exposure controls The information in this section is a gen scenarios that correspond to your ide 8.2.1 Appropriate engineering control Keep away from naked flames/hee 8.2.2 Individual protection measures Observe strict hygiene. Keep controls	e listed below. sing the substance or mixture as intended vailable these will be listed below. Type Long-term systemic effects inhalation Long-term local effects inhalation Long-term systemic effects dermal Acute systemic effects dermal Acute systemic effects inhalation Long-term systemic effects inhalation Long-term systemic effects dermal Acute systemic eff	9 mg/m <sup>3</sup> 3.33 mg/m <sup>3</sup> 1.3 mg/kg bw/day 2.5 mg/kg bw/day 2.5 mg/kg bw/day 2.7 mg/m <sup>3</sup> 2.7 mg/m <sup>3</sup> 0.78 mg/kg bw/day 1.5 mg/kg bw/day  Remark  bosure scenarios are attached in ann haust/ventilation or with respiratory	ex. Always use the relevant expo

		Silirub 2
Respiratory protection r b) Hand protection: Gloves. <u>c) Eye protection:</u> Safety glasses. <u>d) Skin protection:</u> Protective clothing. <b>8.2.3 Environmental expose</b> See headings 6.2, 6.3 an		litions.
ECTION 9: Physical a	and chemical pr	roperties
9.1. Information on basi	c physical and chemic Pa	cal properties
Odour Odour threshold		paracteristic odour
Colour		ariable in colour, depending on the composition
Particle size		o data available
Explosion limits		o data available
Flammability		ot easily combustible ot applicable (mixture)
Log Kow Dynamic viscosity		o data available
Kinematic viscosity		o data available
Melting point	No	o data available
Boiling point		<mark>o data availa</mark> ble
Evaporation rate		o data available
Relative vapour density Vapour pressure		o data available o data available
Solubility		ater ; insoluble
Relative density		1.0
Decomposition tempera		o data available
Auto-ignition temperatu		o data available
Flash point Explosive properties		200 °C o chemical group associated with explosive properties
Oxidising properties		o chemical group associated with explosive properties
pH		p data available
9.2. Other information		
Surface tension	No	o data available
Absolute density		1000 kg/m <sup>3</sup>
ECTION 10: Stability	and reactivity	
10.1. Reactivity	hpoint: higher fire/explosio	n hazard.
10.2. Chemical stability Stable under normal cor		
10.3. Possibility of hazar No data available.		
10.4. Conditions to avoid Precautionary measures Keep away from naked f		
<b>10.5. Incompatible mate</b> No data available.	rials	
10.6. Hazardous decomp Upon combustion: form	oosition products ation of CO, CO2 and small	quantities of nitrous vapours and formation of metallic fumes.
ECTION 11: Toxicolo	ogical informati	on
<b>11.1. Information on tox</b> 11.1.1 Test results	icological effects	
Acute toxicity		
<u>Silirub 2</u> No (test)data on the mixture a	available	
Reason for revision: 15.1		Publication date: 2006-03-13 Date of revision: 2018-01-10

Revision number: 0503

Product number: 43197

Judgement is based on the relevant ingredients

Para	meter	Method	Value		Exposure time	Species		Remark
							determination	
LD50		•	2326 mg/	'kg bw		Rat (male)	Experimental value	
_		-						
LD50		Equivalent to OECD	> 1000 m	g/kg bw	24 h	Rabbit	Experimental value	
		402				(male/female)		
LC50		•	> 4.83 mg	g/l air	4 h	Rat (male/female)	Experimental value	
	LD50 LD50	LD50 LD50 LC50	LD50 Equivalent to OECD 401 LD50 Equivalent to OECD 402	LD50     Equivalent to OECD 401     2326 mg/       LD50     Equivalent to OECD 402     > 1000 m       LC50     Equivalent to OECD     > 4.83 mg/	LD50     Equivalent to OECD 401     2326 mg/kg bw       LD50     Equivalent to OECD 402     > 1000 mg/kg bw       LC50     Equivalent to OECD 402     > 4.83 mg/l air	LD50Equivalent to OECD 4012326 mg/kg bwLD50Equivalent to OECD 402> 1000 mg/kg bwLC50Equivalent to OECD 402> 4.83 mg/l air	LD50       Equivalent to OECD 401       2326 mg/kg bw       Rat (male)         LD50       Equivalent to OECD 402       >1000 mg/kg bw       24 h       Rabbit (male/female)         LC50       Equivalent to OECD 402       >4.83 mg/l air       4 h       Rat (male/female)	LD50     Equivalent to OECD 401     2326 mg/kg bw     Rat (male)     Experimental value       LD50     Equivalent to OECD 402     > 1000 mg/kg bw     24 h     Rabbit (male/female)     Experimental value       LC50     Equivalent to OECD     > 4.83 mg/l air     4 h     Rat (male/female)     Experimental value

#### Conclusion

Not classified for acute toxicity

### Corrosion/irritation

#### <u>Silirub 2</u>

Route of exposure	Result	Method	Exposure time	Time point	Value determination	Remark
	Not irritating	OECD 437			Experimental value	
	Not irrita <mark>ting</mark>				Expert judgement	

Judgement is based on the relevant ingredients

#### 2-butanone oxime

Route of exposure	Result		Method	Exposure tim	ne	Time point		Value determination	Remark
Eye	Serious damage		Equivalent to OECD 405			24; 72 hours	Rabbit	Experimental value	Single treatment
Skin	Slightly	irritating	Other	24 h		1; 24; 48; 72 hours	Rabbit	Experimental value	

### Conclusion

Not classified as irritating to the skin

Not classified as irritating to the eyes

Not classified as irritating to the respiratory system

## Respiratory or skin sensitisation

#### <u>Silirub 2</u>

No (test)data on the mixture available

Judgement is based on the relevant ingredients

2-butanone oxime	
	Decella

Route of exposure	e Result		Method	Exposur	 Observation time point	Species	Value determination	Remark
Skin	Sensitizi	0	Equivalent to OECD 406	24 h		Guinea pig (female)	Experimental value	

#### Conclusion

Not classified as sensitizing for inhalation

Not classified as sensitizing for skin

#### Specific target organ toxicity

#### Silirub 2

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Reason for revision: 15.1

Route of exposu	re Paramete	r Method	Value	Organ	Effect	Exposure time	Species	Value determinatior
Oral	LOAEL	US EPA	40 mg/kg bw/day	General	Clinical signs; mortality; body weight; food consumption	13 weeks (5 days/week)	Rat (male/female)	Experimental value
Oral	NOAEL	US EPA	< 40 mg/kg bw/day	Blood	Change in the haemogramme/ blood composition	13 weeks (5 days/week)	Rat (male/female)	Experimental value
Oral	NOEL	US EPA	125 mg/kg bw/day	Central nervous system	Behavioural disturbances	13 weeks (5 days/week)	Rat (male/female)	Experimental value
Oral	NOAEL	US EPA	312 ppm	Blood	Change in the haemogramme/ blood composition	13 week(s)	Rat (female)	Experimental value
Oral	NOAEL	US EPA	625 ppm	Blood	Change in the haemogramme/ blood composition	13 week(s)	Rat (male)	Experimental value
Inhalation (vapours)	NOAEC	Equivalent to OECD 412	90 mg/m³ air	Blood	Change in the haemogramme/ blood composition	4 weeks (6h/day, 5 days/week)	Rat (male/female)	Experimental value

#### Conclusion

Not classified for subchronic toxicity

## Mutagenicity (in vitro)

<u>Silirub 2</u>

No (test)data on the mixture available

2-butanone oxime

D					
	Result	Method	Test substrate	Effect	Value determination
	Ambiguous		Mouse (lymphoma L5178Y cells)		Experimental value
	Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value
	Negative	Equivalent to OECD 482	Rat liver cells		Experimental value

## Mutagenicity (in vivo)

#### Silirub 2

No (test)data on the mixture available

Judgement is based on the relevant ingredients

#### 2-butanone oxime

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Other	3 day(s)	Drosophila melanogaster (male)	Male reproductive organ	Experimental value
Negative	Other		Rat (male/female)		Experimental value

# Conclusion

Not classified for mutagenic or genotoxic toxicity

## Carcinogenicity

## <u>Silirub 2</u>

No (test)data on the mixture available

Judgement is based on the relevant ingredients

2-but	tanone	oxime
		-

	-							
Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value
exposure								determination
Inhalation	NOAEC	EPA OTS	0.27 mg/l	≥ 1 year(s) (6h/day, 5	Rat	No carcinogenic		Experimental
(vapours)		798.3300		days/week)		effect		value
Inhalation	Dose level	EPA OTS	374 ppm	≥ 1 year(s) (6h/day, 5	Rat	Carcinogenicity	Liver	Experimental
(vapours)		798.3300		days/week)				value

### Conclusion

Not classified for carcinogenicity

# Reproductive toxicity

Si	liru	<u>b 2</u>	

Reason for revision: 15.1

Product number: 43197

No (test)data on the mixture available

Judgement is based on the relevant ingredients

#### <u>2-b</u>

<u>!-bu</u>	<u>tanone oxime</u>								
		Parameter	Method	Value	Exposure time	Species	Effect	· J	Value determination
C	Developmental toxicity	NOAEL (F1)		<mark>600 mg</mark> /kg bw/day	10 day(s)	Rat	No effect		Experimental value
		LOAEL (P)		60 mg/kg bw/day	10 day(s)		Spleen enlargement/aff ection		Experimental value
E	Effects on fertility	NOAEL	US EPA	≥ 200 mg/kg/d		Rat (male/female)			Experimental value

#### Conclusion

Not classified for reprotoxic or developmental toxicity

#### Toxicity other effects

Silirub 2

No (test)data on the mixture available

#### Chronic effects from short and long-term exposure

Silirub 2

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Skin rash/inflammation.

# SECTION 12: Ecological information

# 12.1. Toxicity

# <u>Silirub 2</u>

No (test)data on the mixture available

Judgement of the mixture is based on the relevant ingredients

2-butanone oxime

	Parameter	Method	Value	Duration	Species		Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	> 100 mg/l	96 h	Oryzias latipes	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EC50	OECD 202	201 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	EC50	OECD 201	11.8 mg/l	72 h	Selenastrum capricornutum	Static system	Fresh water	Experimental value; GLP
	NOEC	OECD 201	2.56 mg/l	72 h	Selenastrum capricornutum	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish	NOEC	OECD 204	≥ 100 mg/l	14 day(s)	Oryzias latipes	Flow-through system	Fresh water	Experimental value; GLP
Long-term toxicity aquatic crustacea	NOEC	OECD 211	≥ 100 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; GLP

## **Conclusion**

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

# 12.2. Persistence and degradability

No test data of component(s) available

## 12.3. Bioaccumulative potential

Siliruh 2

SIIIFUD Z						
Log Kow						
Method		Remark		Value	Temperature	Value determination
		Not applic	able (mixture)			
2-butanone oxime						
BCF fishes						
Parameter	Metho	d	Value	Duration	Species	Value determination
BCF	OECD	305	0.5 - 5.8; GLP	42 day(s)	Cyprinus carpio	Experimental value
Log Kow						
Method		Remai	rk	Value	Temperature	Value determination
OECD 117				0.63		Experimental value
Conclusion						
No test data of con	nponent(s)	available				
ason for revision: 15.2	1				Publication dat	te: 2006-03-13
					Date of revisio	n: 2018-01-10
evision number: 0503					Product numb	er: 43197 7 /

## 12.4. Mobility in soil

2-butanone oxime			
(log) Koc			
Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.55	QSAR

#### Conclusion

No (test)data on mobility of the components available

#### 12.5. Results of PBT and vPvB assessment

Due to insufficient data no statement can be made whether the component(s) fulfil(s) the criteria of PBT and vPvB according to Annex XIII of Regulation (EC) No 1907/2006.

#### 12.6. Other adverse effects

#### Silirub 2

Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP) Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

2-butanone oxime

# Groundwater

Groundwater pollutant

# SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 13.1. Waste treatment methods

13.1.1 Provisions relating to waste

#### **European Union**

Can be considered as non hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 04 10 (wastes from MFSU of adhesives and sealants (including waterproofing products): waste adhesives and sealants other than those mentioned in 08 04 09). Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

#### 13.1.3 Packaging/Container

#### **European Union**

Waste material code packaging (Directive 2008/98/EC).

15 01 02 (plastic packaging).

# SECTION 14: Transport information

# Road (ADR), Rail (RID), Inland waterways (ADN), Sea (IMDG/IMSBC), Air (ICAO-TI/IATA-DGR)

14.1 LIN number

Transport		Not subject	
14.2. UN proper shipping na	me		
14.3. Transport hazard class	(es)		
Hazard identification nu	mber		
Class			
Classification code			
14.4. Packing group			
Packing group			
Labels			
14.5. Environmental hazard			
Environmentally hazard	ous substance mark	no	
14.6. Special precautions for	user		
Special provisions			
Limited quantities			
14.7. Transport in bulk acco	rding to Annex II of Marpol and the IBC Code		
Annex II of MARPOL 73/	78	Not applicable, based on available data	
n for revision: 15.1		Publication date: 2006-03-13	
n for revision: 15.1		Publication date: 2006-03-13 Date of revision: 2018-01-10	

TION 15: Regulate 5.1. Safety, health and e	nvironmental regulations/legislation sp	ecific for the substance or mixture
European legislation:		
VOC content Directive 201	D/75/EU	
VOC content		Remark
< 1.014 %		
< 10.14 g/l		
REACH Annex XVII - Rest	iction	
		n (EC) No 1907/2006: restrictions on the manufacture, placing on the mar
	agerous substances, mixtures and articles.	
		nditions of restriction
2-butanone oxime	substances or of the mixture           Liquid substances or mixtures which are         1.5	Shall not be used in:
	criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: 077 (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 and 2, 2.14 categories 1 and 2, 2.13 categories 13.5 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1. (d) hazard class 5.1. (entities and the set of the set of the set of the set of the by child and the set of the set of the set of th	ases, for example in ornamental lamps and ashtrays, tricks and jokes, games for one or more participants, or any article intended to be used as such, even namental aspects, Articles not complying with paragraph 1 shall not be placed on the market. Shall not be placed on the market if they contain a colouring agent, unless required for cal reasons, or perfume, or both, if they: can be used as fuel in decorative oil lamps for supply to the general public, and, present an aspiration hazard and are labelled with R65 or H304, Decorative oil lamps for supply to the general public shall not be placed on the market less they conform to the European Standard on Decorative oil lamps (EN 14059) ado the European Committee for Standardisation (CEN). Without prejudice to the implementation of other Community provisions relating to sisfication, packaging and labelling of dangerous substances and mixtures, suppliers is sure, before the placing on the market, that the following requirements are met: lamp oils, labelled with R65 or H304, intended for supply to the general public are vis gibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the rea idren"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of nps — may lead to life- threatening lung damage"; grill lighter fluids, labelled with R65 or H304, intended for supply to the general publi gibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter fluids and cordianes, labelled with R65 or H304, intended for supply to the general publi gibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter fluids and grill lighters, labelled with R65 or H304, intended for supply to the general public grepare a dossier, in accordance with Article 69 of the present Regulation with a view n, if appropriate, grill lighters fluids and fuel for decorative lamps, labelled R65 or H304 ended for supply to the general public. Natural or legal persons placing on the market for the first ti
National logislation Polaium		
National legislation Belgium Silirub 2		
No data available		
National legislation The Net	herlands	
<u>Silirub 2</u>		
Waterbezwaarlijkheid	B (4)	
National legislation France		
<u>Silirub 2</u>		
No data available		
National legislation German	Y	
Silirub 2		
WGK		e components in compliance with Verwaltungsvorschrift wassergefährder and Verordnung über Anlagen zum Umgang mit wassergefährdenden Stof
	(AwSV) of 18 April 2017	
2-butanone oxime		
TA-Luft	5.2.5; 1	
TRGS900 - Risiko der Fruchtschödigung		g braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologische
Fruchtschädigung Sensibilisierende Stoffe	Grenzwertes nicht befürchtet zu werden Butanonoxim; Sh; Hautsensibilisierende Sto	ffe
Hautresorptive Stoffe	Butanonoxim; H; Hautresorptiv	
- f		
on for rougion: 1E 1		Publication date: 2006-03-13
on for revision: 15.1		Date of revision: 2018-01-10

	Silirub 2	
National legislation U	nited K <mark>ingdom</mark>	
<u>Silirub 2</u> No data available		
Other relevant data		
Silirub 2		
No data available		
15.2. Chemical safet No chemical safety	y assessment assessment has been conducted for the mixture.	
CTION 16: Othe	r information	
=	ements referred to under heading 3:	
H312 Harmful in c	ontact with skin. an allergic skin reaction.	
H318 Causes serio	5	
H351 Suspected o		
(*) (*)	INTERNAL CLASSIFICATION BY BIG	
CLP (EU-GHS) DMEL	Classification, labelling and packaging (Globally Harmonised Sys Derived Minimal Effect Level	stem in Europe)
DNEL	Derived Minima Effect Level	
EC50	Effect Concentration 50 %	
ErC50	EC50 in terms of reduction of growth rate	
LC50	Le <mark>thal Concentration 50 %</mark>	
LD50	Lethal Dose 50 %	
NOAEL	No Observed Adverse Effect Level	
NOEC OECD	No Observed Effect Concentration Organisation for Economic Co-operation and Development	
PBT	Persistent, Bioaccumulative & Toxic	
PNEC	Predicted No Effect Concentration	
STP	Sludge Treatment Process	
vPvB	very Persistent & very Bioaccumulative	
state of knowledge of the substances/ may be used. Old v substances/prepar substances/prepar take all measures of circumstances. BIG parties. This safety in other countries, local legislation. Us failing the general	this safety data sheet is based on data and samples provided to BIG at that time. The safety data sheet only constitutes a guideline for to preparations/mixtures mentioned under point 1. New safety data sh ersions must be destroyed. Unless indicated otherwise word for wo ations/mixtures in purer form, mixed with other substances or in pr ations/mixtures in question. Compliance with the instructions in this lictated by common sense, regulations and recommendations or wh does not guarantee the accuracy or exhaustiveness of the informat data sheet has been elaborated for use within the European Union, where local legislation with regards to the set-up of safety data sheet e of this safety data sheet is subject to the licence and liability limitic conditions of BIG. All intellectual property rights to this sheet are the	the safe handling, use, consumption, storage, transport and dispose neets are written from time to time. Only the most recent versions and on the safety data sheet, the information does not apply to occesses. The safety data sheet offers no quality specification for the safety data sheet does not release the user from the obligation to nich are necessary and/or useful based on the real applicable cion provided and cannot be held liable for any changes by third , Switzerland, Iceland, Norway and Lichtenstein. It may be consulte ets will take precedence. It is your obligation to verify and apply su ng conditions as stated in your BIG licence agreement or when this
Consult the mentio	aned agreement/conditions for details.	
con for revision 45 4		Publication date: 2006.02.12
ion for revision: 15.1		Publication date: 2006-03-13

Revision number: 0503

Product number: 43197

Date of revision: 2018-01-10